

UK Declaration of Performance

Kingspan Thermarroof® TR27

1000.UKDoP.TR27.002

1001.UKDoP.TR27.002

Unique identification code of the product-type:

Intended use/es:

Manufacturer:

System/s of AVCP:

Designated technical specification:

UK Assessment body/ies:

Thermarroof® TR27

Thermal insulation for buildings

Kingspan Insulation Ltd, Herefordshire HR6 9LA,UK

System 4 (Reaction to fire), System 3 (Other Properties)

BS-EN 13165:2012+A2:2016

University of Salford :1145, BITS: 1334

Essential characteristics		Performance	
Thermal resistance	Thermal resistance R_D ((m ² .K)/W)	d_N 30mm	1.10
		d_N 40mm	1.45
		d_N 50mm	1.85
d_N 60mm		2.20	
d_N 70mm		2.55	
d_N 80mm		3.20	
d_N 90mm		3.60	
d_N 100mm		4.00	
d_N 120mm		5.00	
d_N 130mm		5.40	
d_N 140mm	5.80		
d_N 150mm	6.25		
d_N 160mm	6.65		
Thermal resistance	Thermal conductivity λ_D (W/(m.K))	$d_N < 80$ mm	0.027
		d_N 80-119mm	0.025
		$d_N \geq 120$ mm	0.024
Thermal resistance	Thickness tolerance	T2	
		F	
		NPD	
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability of the reaction to fire of the product as placed on the market	NPD	
	Durability of thermal resistance and thermal conductivity against ageing/ degradation	NPD	
Durability of Thermal Resistance against heat, weathering, ageing / degradation	Thermal resistance R_D ((m ² .K)/W)	Thermal resistance as table above	
	Thermal conductivity λ_D (W/(m.K))	$d_N < 80$ mm	0.027
		d_N 80-119mm	0.025
		$d_N \geq 120$ mm	0.024
	Durability characteristics	NPD	
Durability of Thermal Resistance against heat, weathering, ageing / degradation	Dimensional stability under specified temperature and humidity condition	DS(70,90)3 DS(-20,-)1	
	Deformation under specified compressive load and temperature conditions	NPD	

UK Declaration of Performance

	Determination of the aged values of thermal resistance and thermal conductivity	λD 0,024, 0.025, 0,027 W/m-K
Compressive strength	Compressive stress or compressive strength	CS(10\Y)150
Tensile / Flexural strength	Tensile strength perpendicular to faces	TR80
Durability of compressive strength against ageing / degradation	Compressive creep	NPD
Water permeability	Short term water absorption	NPD
	Long term water absorption	NPD
	Flatness after one sided wetting	NPD
Water vapour permeability	Water vapour transmission	NPD
Acoustic absorption index	Sound absorption	NPD
Continuous Glowing Combustion	Glowing Combustion	NPD
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD
NPD: No Performance Determined		

EU Regulation 305/2011, as retained in UK law, and as amended by SI no. 465/2019 (the Construction Products (Amendment etc.) (EU Exit) Regulations 2019) and SI no. 1359/2020 (the Construction Products (Amendment etc.) (EU Exit) Regulations 2020.)

Signed for and on behalf of the manufacturer by:



.....
Ralph Mannion
Managing Director
Pembridge, Selby England, UK
Date signed: 18/01/2022
Issue Number: 002

K:\GB\UKDoP\TR27\002\Jan22a