



UK Declaration of Performance

Thermaroof® TR26

1000.UKDoP.TR26.003

1001.UKDoP.TR26.003

Thermaroof ® TR26 Unique identification code of the product-type: Thermal insulation for buildings

Intended use/es:

Kingspan Insulation Ltd, Herefordshire HR6 9LA,UK Manufacturer: System/s of AVCP: System 4 (Reaction to fire), System 3 (Other Properties)

Designated technical specification: BS-EN 13165:2012+A2:2016

UK Assessment body/ies: University of Salford: 1145,, B.I.T.S: 1334

Essential characteristics		Performance
Essential characteristics		d _N 20mm
Thermal resistance	Thermal resistance R _D ((m².K)/W)	d _N 20mm 0.95
		d _N 40mm 1.80
		d _N 50mm 2.25
		d _N 60mm 2.70
		d _N 70mm 3.15
		d _N 80mm 3.60
		d _N 90mm 4.05
		d _N 100mm 4.50
		d _N 120mm 5.45
		d _N 130mm 5.90
		d _N 140mm 6.35
		d _N 150mm 6.80
		d _N 160mm 7.25
		d _N 20mm 0.022
	Thermal conductivity λ _D (W/(m.K))	d _N 160mm
	Thickness tolerance	T2
Reaction to fire	Reaction to fire	
Reaction to file	Reaction to life	F
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability of the reaction to fire of the	NDD
	product as placed on the market	NPD
	F	
		NDD
	Durability of thermal resistance and	NPD
	thermal conductivity against ageing/	
	degradation	
Durability of Thermal Resistance against heat, weathering, ageing / degradation		
	Thermal resistance R _D ((m².K)/W)	The most as a fatour as a second second
	2 ((),)	Thermal resistance as table above
	Thermal conductivity λD (W/(m.K))	0.022
	Durability characteristics	NPD
		· · · -
		DS(70,90)3
3. 3 3	Dimensional stability under specified	DS(70,90)3 DS(-20,-)1
	temperature and humidity condition	DO(-20,-)1
	Deformation under specified	NPD
	compressive load and temperature	
	conditions	





UK Declaration of Performance

			
	Determination of the aged values of thermal resistance and thermal conductivity	λD 0,022 W/m·K	
Compressive strength	Compressive stress or compressive strength	CS(10\Y)150	
Tensile / Flexural strength	Tensile strength perpendicular to faces	TR40	
Durability of compressive strength against ageing / degradation	Compressive creep	NPD	
Water permeability	Short term water absorption	NPD	
	Long term water absorption	NPD	
	Flatness after one sided wetting	NPD	
Water vapour permeability	Water vapour transmission	NPD	
Acoustic absorption index	Sound absorption	NPD	
Continuous Glowing Combustion	Glowing Combustion	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD	
NPD: No Performance Determined			

EU Regulation 305/2011, as retained in UK law, and as amended by SI no. 465/2019 (the Construction Products (Amendment etc.) (EU Exit) Regulations 2019) and SI no. 1359/2020 (the Construction Products (Amendment etc.) (EU Exit) Regulations 2020.)

Signed for and on behalf of the manufacturer by:

Ralph Mannion . Managing Director

Pembridge &Selby ,England, UK Date signed: 18/01/2022

Issue Number: 003

KI\GB\UKDoP\TR26\003\Jan22a